

# LMR 400 Plenum Cable

SKU: 952002

## FEATURES

- UL rated CMP/FT6
- Flexible conductor enables tight bend radius
- Low-loss coaxial cable for wireless applications
- For indoor plenum use (dropped ceilings and raised floors)
- Meets all code requirements for installation in plenum air handling spaces



952002 LMR 400 Plenum Cable shown

## Specifications

### LMR 400 Plenum Cable

Dielectric Insulation	PTFE
Center Conductor Material	Copper Clad Aluminum
Center Conductor Diameter	.100 in
Center Conductor Construction	Solid
Nominal Core O.D.	0.285 in
Nominal O.D.	0.405 in
VOP	76%
Shield %	100% foil 90% braid
Nominal Capacitance (pF/ft)	27
Attenuation	dB/100ft
Loss @ 50 MHz	1.00 dB

### (Con't LMR 400 Plenum Cable)

Loss @ 100 MHz	1.35 dB
Loss @ 400 MHz	2.74 dB
Loss @ 900 MHz	4.2 dB
Loss @ 1000 MHz	4.39 dB
Loss @ 1800 MHz	5.7 dB
Loss @ 2500 MHz	6.8 dB
Jacket Color	Orange Jacket
Mfg. Warranty	5 Years
Jacket Material	FRPVC
Rating	UL/CMP
Braid Material	Tinned Copper

## Support



2 Year Warranty

**Email:** [support@wilsonelectronics.com](mailto:support@wilsonelectronics.com)

**Website:** <http://support.weboost.com>

**Phone:** +1 866 294 1660  
Monday to Saturday